



Monocrystalline Silicon Solar PV Modules

Product Feature

High Efficiency

Excellent Performance

Long Life Span

Low Temperature Coefficient

High Power Output

Low Temperature Coefficient

High Power Output

Low Temperature Coefficient

High Power Output

Low Temperature Coefficient

High Power Output

Low Temperature Coefficient

High Power Output

Low Temperature Coefficient

High Power Output

Low Temperature Coefficient

High Power Output

Low Temperature Coefficient

High Power Output

Low Temperature Coefficient

High Power Output

Low Temperature Coefficient

High Power Output

Low Temperature Coefficient

High Power Output

Low Temperature Coefficient

High Power Output

Low Temperature Coefficient

High Power Output

Low Temperature Coefficient

High Power Output

Low Temperature Coefficient

High Power Output

Low Temperature Coefficient

High Power Output

Low Temperature Coefficient

High Power Output

Low Temperature Coefficient

High Power Output

Low Temperature Coefficient

High Power Output

Low Temperature Coefficient

High Power Output

Low Temperature Coefficient

High Power Output

Low Temperature Coefficient

High Power Output

Low Temperature Coefficient

High Power Output

Low Temperature Coefficient

High Power Output

Low Temperature Coefficient

High Power Output

Low Temperature Coefficient

High Power Output

Low Temperature Coefficient

High Power Output

Low Temperature Coefficient

High Power Output

Low Temperature Coefficient

High Power Output

Low Temperature Coefficient

High Power Output

Low Temperature Coefficient

High Power Output


Low Temperature Coefficient

High Power Output

Low Temperature Coefficient

High Power Output

Low Temperature Coefficient



采用先进的制造工艺，组件效率最高达 21%。

正公差

1. 5 放 行 法 琴 聲 清 亮 如 玉 二 遍 保 紙 律 兩 次 奏 響

[illegible][illegible]

良好的設計規範

西田鞋作市所工研鞋造有限



五、**“五五”期间，计划安排**

Abstract

1. GB/T24001-2016

2001-2007 / CREDIT 2001-2011

~~L331720、L331730、L331740、CQC、ZHEJIANG MADE~~

107889162555


ISO 14001:2015

QHS4S1

150

组件尺寸

机械参数



组件尺寸 2279*1134*35mm

电池片类型 单晶硅 182mm

电池片数量 144片/组件

功率峰值 210Wp

高透 EVA

封装

1134 2279 35

图 1 光伏组件